



835 HURRI-KLEEN™

DESCRIPTION

HURRI-KLEEN™ is a non-corrosive water-based rubber softener and remover.

USES

HURRI-KLEEN™ will remove all types of unattractive rubber created by cars, trucks, golf carts, aircraft and lift trucks.

HURRI-KLEEN™ will remove rubber from any surface.

PREPARATION AND APPLICATION

For small areas: Dilute 1 part **HURRI-KLEEN™** to 3 parts water and apply liberally to surface. Agitate with a stiff brush and let stand for 5 to 10 minutes, then flush with clean water before it dries.

Runways: Mix 1 part **HURRI-KLEEN™** to 3 parts water and thoroughly soak the area. Agitate with sweeper for 5 to 10 minutes. Flush with power washer and repeat if necessary. Never allow the surface to dry until it is clean.

COVERAGE

100 ft²/ US gal (2.45 m²/L)

Q&A

Shelf life is indefinite

SAFETY

Please refer to SDS at spggogreen.com or Contact SPG

HURRI-KLEEN™ will improve the friction of the surface by removing the rubber.

FEATURES

- Unique formulation that can be ready to use or cut to desired levels
- Non-flammable
- 100% water soluble
- pH neutral
- 100 % biodegradable
- An effective maintenance option
- **HURRI-KLEEN™** will not harm plastic, glass, aluminum or fiberglass

WARRANTY DISCLAIMER

The information herein is to assist customers in determining whether our products are suitable for their application. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to the contents and suitability. We warrant that our products will meet our written specifications. Nothing herein shall constitute a warranty expressed or implied including any warranty of merchantability of fitness, nor is protection from any loss or patent to be inferred. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.