



950 Coal Ash Solidify™

DESCRIPTION

Coal Ash Solidify is an environmentally friendly dewatering system for coal ash slurry. This granular powder containing post-consumer recycled material to consolidate the coal ash slurry making it easily portable by mechanical means.

BASIC USES

Used in the dewatering of coal ash slurry 950 provides rapid safe removal to storage, disposal or recycling sites.

MAJOR ADVANTAGES OF Coal Ash Solidify™

- Solidification mitigates negative effect of coal ash in ground water
- Contains post-consumer recycled content
- Non-toxic
- Environmentally friendly
- Reduces or eliminates the need for cement or LKD required to attempt to stabilize coal ash
- Requires a minute amount to cause solidification
- Acts rapidly to solidify coal ash slurry
- Highly Compactable
- Reduces Carbon Footprint
- Contains post-consumer recycled content
- Dewateres Construction Sites

METHOD OF USE

Apply Coal Ash Solidify using mechanical spreaders per the below volumetric application quantities.

FOR CALCULATING COAL ASH SOLIDIFY REQUIRED FOR 1 ACRE/FT
4350 lb (1973 kg) or about 2 MT (approx. 2 bags) are required.
Per square yard (1 ft depth): 0.9 lb. (0.41 kg)

Available Packaging: Super Sacks

Storage: Keep under cover out of sun and rain

Temperature range of use: This product has no limit to the temperature range however it may be limited by the material it treats.

SAFETY

Please refer to the SDS at www.spggogreen.com. Use the same precautions as when working with conventional cement for coal ash removal. Although the material is non-toxic, it is good practice to protect exposed skin areas and to wear a face mask to prevent inhalation of the aggregate particles.

WARRANTY DISCLAIMER

The information herein is to assist customers with product selection. Our products are intended for sale to qualified industrial and commercial Customers. Customers shall be responsible for inspection of product prior to use to determine suitability for and applicability to their application. Trial batch mixes are encouraged with certified ready-mix providers. We warrant that our products will meet our written specifications. Nothing herein shall constitute a warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any loss or patent to be inferred. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental, or consequential damages. Project specific warranties are available for waterproofing and concrete durability.

TECHNICAL & PRODUCT DATA

- Appearance: Off White
- Odor: No Odor
- Toxicity: No Toxicity
- pH: Neutral
- Shelf Life: 1 Year
- Hazardous Vapors: None
- Number of Components: 1