



SPECIALTY
PRODUCTS
GROUP

856 STRIP THIS TOO™ SEMI PASTE 858 STRIP THIS TOO™ LIQUID

DESCRIPTION

856STRIP THIS TOO!™ is a semi-paste paint and varnish remover with a proprietary blend of cutting agents, waxes and thickening agents. These waxes seal in the cutting agents after being applied and allow the product to stay wet for an extended period of time; making it possible to remove multiple coats of paint or varnish with only one application.

BASIC USES

Will remove latex, oil based enamels, epoxy, coal tar epoxy, urethanes, polyurethane, shellac, varnish, lacquers, elastomeric and clear coats from wood, metal, brick, concrete, fiberglass, glass and stone. **856 STRIP THIS TOO!™** is an above average product for graffiti removal.

TECHNICAL AND PRODUCT DATA

- Completely Free of VOCs. odorless, solvent-free and biodegradable.
- Safe for use on wood, fiberglass, glass, concrete, limestone and all metals
- pH neutral and does not need to be neutralized after use, prior to recoating
- Will cling to vertical and horizontal surfaces including ceilings without dripping.
- Will remain wet much longer than conventional strippers allowing it to perform more effectively.
- Will not harm glue or veneer and is safe for refinishing fine furniture and antiques.
- Contains no methylene chloride, acids or caustics.
- Meets Environment Canada's Eco Logo requirements for paint strippers and meets California's Rule 66.
- Is an above average graffiti remover.
-

MAJOR ADVANTAGES OF STRIP THIS TOO™ SEMI PASTE

- VOC free.
- pH neutral.
- Clings to vertical or horizontal surfaces.
- Remains wet longer to allow better performance.
- Doesn't harm glue or veneer.
- Safe for refinishing furniture.
- Doesn't Contain acids, caustics or methylene chloride.
- Meets Environment Canada's Eco Logo requirements.
- Meets California's Rule 66.
- An above average graffiti remover.



SPECIALTY
PRODUCTS
GROUP

856 STRIP THIS TOO™ SEMI PASTE 858 STRIP THIS TOO™ LIQUID

APPLICATION INSTRUCTIONS

856 STRIP THIS TOO!™ can be brushed, trowelled or sprayed on. When brushing, lay an even coat of stripper on the surface.

DO NOT BRUSH OUT.

When trowelling lay an even 1/16th inch coat over the entire surface.

When spraying, spray an even coat of approximately 1/16th over entire surface.

On all 3 applications you must allow the product to perform before you break the surface of the stripper to start your clean up.

A typical strip time for most coatings is between 2 to 4 hours on average. Leaving **856 STRIP THIS TOO!**™ to work longer will result in much less scraping and cleaning. Let the stripper do the work for you.

SPRAY EQUIPMENT

Use a quality airless spray gun with a .055 orifice and pressure between 40 to 60 psi. Keep compressor away from work area.

COVERAGE

Coverage: 100 square feet/gallon (2.45 m²/L)

CLEAN UP

Use **858 STRIP THIS TOO!**™ LIQUID and Scotch Brite pads to clean surface of any residue and to clean up all your equipment.



SPECIALTY
PRODUCTS
GROUP

856 STRIP THIS TOO™ SEMI PASTE 858 STRIP THIS TOO™ LIQUID

FEATURES

- Removes graffiti on painted surfaces without removing the base coat. Saves time and money because there is no need to repaint.
- Excellent for the final clean up of wood. It removes the paint from the grain, beautifies the wood and prepares it for re-coating.
- Cost effective as a brush cleaner, rejuvenates old brushes.
- An ideal product for cleaning small parts and large scale refinishing using dip tanks.
- Ideal for cleaning spray equipment, lines and hoses.

MAJOR ADVANTAGES OF STRIP THIS TOO™ LIQUID

- Removes graffiti and leaves base coat.
- Excellent for cleaning wood grain in preparation for recoating.
- Cost effective brush cleaner.
- Bring old brushes back to life.
- Good for cleaning small parts, large scale refinishing using dip tanks.
- Cleans spray equipment, lines and hoses.

SAFETY PRECAUTIONS

Avoid eye and skin contact. Never use near open flames, electrical or sparks.

Wear protective safety equipment, gloves, goggles and respirator, if necessary.

ALWAYS VENTILATE THE AREA WITH FRESH AIR.

SAFETY

Please refer to SDS at spggogreen.com or contact SPG.

WARRANTY DISCLAIMER

The information herein is to assist customers with product selection. Our products are intended for sale to qualified industrial and commercial customers. Customers shall be responsible for inspection of product prior to use to determine suitability for and applicability to their application. Trial batch mixes are encouraged with certified ready mix providers. We warrant that our products will meet our written specifications. Nothing herein shall constitute a warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any loss or patent to be inferred. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages. Project specific warranties are available for waterproofing and concrete durability. Contact SPG prior to installation for project specific warranty registration and requirements.

