

# SAFETY DATA SHEET

#### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

PRODUCT NAME	VAPOR LOCK SCS 120 <sup>TM</sup>		
PRODUCT USE	Water-based concrete admixture that stops the route of moisture migration		
MANUFACTURER'S NAME	Specialty Products Group		
	6254 Skyway Rd, PO Box 915	Tel 1-877-957-4626	3909 Witmer Rd Suite 1014
	Smithville ON LOR 2A0	Fax 1-905-527-0606	Niagara Falls NY 14305
EMERGENCY NUMBER	613-996-6666 OR *666 CANUTEC		
	1-800-535-5053 UNITED STATES POISON INFORMATION CENTRE		

### 2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION: Flammability 5, Reactivity 5, Health 4

ROUTE OF ENTRY	Eye contact, Ingestion, Inhalation, Skin contact.
CARCINOGENIC STATUS	Not considered carcinogenic by NTP, IARC, and OSHA.
TARGET ORGANS	Eye, Skin, and lungs
HEALTH EFFECTS – EYE	Moderate irritation expected
HEALTH EFFECTS – SKIN	Moderate irritation expected.
HEALTH EFFECTS – INGESTION	May cause irritation to the mouth, esophagus and stomach and damage to kidney, central nervous system and
	blood.
HEALTH EFFECTS – INHALATION	Spray mist is irritating to the respiratory system.

# **3.COMPOSITION/INFORMATION ON INGREDIENTS**

Ingredients are non-hazardous and proprietary

# 4. FIRST AID MEASURES

FIRST AID – INHALATION	No inhalation hazard expected.	
FIRST AID – SKIN Rinse skin with water. Remove contaminated clothing and shoes.		
FIRST AID – EYE Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention.		
FIRST AID – INGESTION If swallowed, rinse mouth with water if discomfort or diarrhea persist call for medical assistance.		
INFORMATION FOR DOCTOR		
Most important symptoms and effects, both acute and delayed.		
No further relevant information		
Indications of any immediate medical attention and energial treatment needed		

Indications of any immediate medical attention and special treatment needed.

No further relevant information available.

# 5. FIRE FIGHTING MEASURES

CONDITIONS OF FLAMMABILITY	Non-flammable. Will not support combustion.
EXTINGUISHING MEDIA	Is compatible with all extinguishing media.
SPECIAL HAZARDS OF PRODUCT	Dries to powdery material.
PROTECTIVE EQUIPMENT FOR FIRE FIGHTING	N/A
EXPLOSION DATA – SENSITIVITY TO IMPACT	N/A
EXPLOSION DATA – SENSITIVITY TO STATIC DISCHARGE	N/A

# 6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES	Small spills – Mop up and allow to enter drain or dispose of in accordance with federal, provincial and local regulations or permits. Large spills: dispose of in accordance with federal, provincial and local regulations or permits. No special requirements.		
PERSONAL PRECAUTIONS	Minimize exposure		
ENVIRONMENTAL PRECAUTIONS	/IRONMENTAL PRECAUTIONS Unless for intended use, prevent entry into water system		
REFERENCES TO OTHER SECTIONS			

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment

See Section 13 for disposal information

#### HANDLING AND STORAGE 7.

HANDLING

STORAGE

Avoid contact with eyes, skin and clothing. Keep container closed. Keep container closed. Store in plastic containers. INFORMATION ABOUT PROTECTION AGAINST EXPLOSION AND FIRE

Not a fire or explosive hazard

SPECIFIC END USE(S)

No further relevant information available

#### **EXPOSURE CONTROLS/PERSONAL PROTECTION** 8.

ENGINEERING CONTROL MEASURES	Use with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within direct access.
RESPIRATORY PROTECTION	None
HAND PROTECTION	Wash hands after use
EYE PROTECTION	Avoid splashing or spray into eyes
BODY PROTECTION	Avoid body contact – wash or rinse any sprayed area
PROTECTION DURING APPLICATION	No special protection required

9. PHYSICAL AND CHEMICAL PROPERTIES		
PHYSICAL STATE	Liquid	
ODOUR & APPEARANCE	Light green liquid	
ODOR THRESHOLD (ppm)	NA	
SPECIFIC GRAVITY	1.3 -1.35	
VAPOR DENSITY (AIR = 1)	ND	
VAPOR PRESSURE at 20°C	ND	
EVAPORATION RATE	ND	
BOILING POINT (°C/°F)	100°C (212°F)	
FREEZING POINT (°C/°F)	ND	
рН	10-12	
COEFFICIENT OF WATER/OIL DISTRIBUTION	6.5 -7.5	
SOLUBILITY IN WATER	Miscible	
VOC (g/L)	0	
FLASH POINT (PMCC) (°C/°F)	Non-flammable.	
UPPER FLAMMABLE LIMIT %VOL	NA	
LOWER FLAMMABLE LIMIT %VOL	NA	
AUTOIGNITION TEMP (°C/°F)	NA	

# **10. STABILITY AND REACTIVITY**

STABILITY	Stable under normal conditions
CONDITIONS TO AVOID	Do Not Freeze
MATERIALS TO AVOID	None
HAZARDOUS POLYMERIZATION	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS	None

# **11. TOXICOLOGICAL INFORMATION**

EFFECTS OF ACUTE EXPOSURE	Irritation to the eyes and skin is expected. Mild irritation to mouth, throat, nausea, vomiting, and abdominal pain. On inhalation of liquid will cause irritation to mucous membranes.
EFFECTS OF CHRONIC EXPOSURE	NA
EXPOSURE LIMITS	NA
IRRITANCY	Moderate irritation expected
SENSITIZATION	ND
CARCINOGENICITY	Not listed as a carcinogen by IARC, NTP or OSHA.
REPRODUCTIVE TOXICITY	ND
TERATOGENICITY	ND
MUTAGENICITY	ND
TOXICOLOGICALLY SYNERGISTIC PRODUCTS	ND

#### VAPOR LOCK™ SCS 120

### 12. ECOLOGICAL INFORMATION

MOBILITY	Completely miscible with water
PERSISTENCE/DEGRADABILITY	This product is not persistent in aquatic systems
BIO-ACCUMULATION	Not know to bio-accumulate
ECOTOXICITY	None known

#### **13. DISPOSAL CONSIDERATIONS**

 PRODUCT DISPOSAL
 Dispose of in accordance with all applicable local and national regulation. No special method required

 CONTAINER DISPOSAL
 Labels should not be removed from containers until they have been cleaned.

 UNCLEANED PACKAGINGS
 Recommendation: No special method required

# 14. TRANSPORTATION INFORMATION

CANADA	TDG CLASSIFICATION	
HAZARD LABEL NOT REQUIRED	NOT REGULATED, Keep from freezing	
EXPORT		
DOT CFR 172.101 DATA	NOT REGULATED	
UN PROPER SHIPPING NAME	NA	
UN CLASS	NA	
UN NUMBER	NA	
UN PACKAGING GROUP	NA	
FLASH POINT	NA	
HAZARDOUS MATERIAL	NA	
HAZARD LABEL	NA	
MARINE POLLUTANT	NA	
SPECIFIC PRECAUTIONS FOR USER	NA	

#### **15. REGULATORY INFORMATION**

#### WHMIS CLASSIFICATION: Not regulated

CEPA STATUS (DSL): All of the ingredients of this product are listed on the Domestic Substances List.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by CPR.

#### VAPOR LOCK<sup>™</sup> SCS 120

16. OTHER INFORMATION			
HMIS	S hazard ID:		NFPA hazard ID:
FLAMMABILITY 0 2-MC REACTIVITY 0 3-SE	NIMAL; IGHT; DDERATE; RIOUS; VERE	PROTECTIVE ROUTIVENT	0-MINIMAL; 1-SLIGHT; 2-MODERATE; 3-SERIOUS; 4-SEVERE
KEY	NA: No applicabl	e information found or available	
		stracts Service Number	
		nference of Governmental Industrial	Hygienists
		Safety and Health Administration	
	TLV: Threshold Li		
		Exposure Limit	
		Short Term Exposure Limit National Toxicology Program	
		International Agency for Research on Cancer	
	R: Risk S: Safety		
	LD50: Lethal Dose	50%	
		entration 50%	
PREPARED BY:	Specialty Products Group Inc.		
SDS REVISION DATE	November 1, 2023		

Provided data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable, however, each user should review these recommendations.